



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ³: A62C 33/02; F26B 9/06	A1	(11) International Publication Number: WO 81/00965 (43) International Publication Date: 16 April 1981 (16.04.81)
<p>(21) International Application Number: PCT/SE80/00247</p> <p>(22) International Filing Date: 8 October 1980 (08.10.80)</p> <p>(31) Priority Application Number: 7908321-8</p> <p>(32) Priority Date: 8 October 1979 (08.10.79)</p> <p>(33) Priority Country: SE</p> <p>(71) Applicants; and (72) Inventors: WAHLSTRÖM, Hans, Vilhelm [SE/SE]; Bergåsstigen 3, S-182 33 Danderyd (SE). NILSSON, Rolf, Elon [SE/SE]; Uttervägen 9, S-195 00 Märsta (SE). PIHLGREN, Kjell, Åke [SE/SE]; Huginvägen 48, S-194 00 Upplands Väsby (SE).</p> <p>(74) Agent: ZETTERSTRÖM, Alf; Alf Zetterström AB, Brahegatan 30, S-114 37 Stockholm (SE).</p>		<p>(81) Designated States: AT, DE, FI, GB, JP, NO.</p> <p>Published <i>With international search report</i></p>
<p>(54) Title: A DRIER FOR DRYING FIRE-HOSES OR OTHER SIMILAR HOSES</p> <p>(57) Abstract</p> <p>A drier for drying fire-hoses or other similar hoses comprises an elongated horizontal receptacle (10), in which a plurality of hoses (19) may be placed side by side in extended positions to undergo drying in said receptacle. In order to permit a continuous operation of the drier, said receptacle (10) is divided into two parallel drying chambers (11), extending in side by side relationship along the length of the receptacle. At their upper ends, said drying chambers (11) have longitudinally extending openings which are individually closable by means of appurtenant covers (13). The two covers (13) are rigidly mounted on a common rotatable shaft (14), located between them and connected to a single driving motor (16). Additionally, the two covers (13) act as counterweights for each other to reduce the required driving power.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	KP	Democratic People's Republic of Korea
AU	Australia	LI	Liechtenstein
BR	Brazil	LU	Luxembourg
CF	Central African Republic	MC	Monaco
CG	Congo	MG	Madagascar
CH	Switzerland	MW	Malawi
CM	Cameroon	NL	Netherlands
DE	Germany, Federal Republic of	NO	Norway
DK	Denmark	RO	Romania
FI	Finland	SE	Sweden
FR	France	SN	Senegal
GA	Gabon	SU	Soviet Union
GB	United Kingdom	TD	Chad
HU	Hungary	TG	Togo
JP	Japan	US	United States of America

BEST AVAILABLE COPY

A drier for drying fire-hoses or
other similar hoses

The present invention relates to a drier for drying fire-hoses or other similar hoses. More particularly, the invention relates to such a drier, comprising an elongated horizontal receptacle in which a plurality
5 of wet hoses may be placed side by side in extended positions to undergo drying in said receptacle upon closure of the space in which the hoses have been placed.

In practice, a drier of said kind usually forms part of a complete hose cleaning plant, also including a
10 washing equipment, located at one end of said receptacle. Hoses to be cleaned are drawn slowly one by one through said washing equipment and are then laid down in the receptacle of the drier through a longitudinal opening, provided at the upper end of said receptacle. When a
15 drying process is to be initiated, said opening is closed by means of a suitable cover. The washing operation successively performed on the hoses as well as the step of laying down the hoses in the receptacle takes considerable time. Additional time is spent on testing
20 the hoses, before the drying process can be started. In prior art driers of the above kind, said time consumption has resulted in a considerable restriction of the time during which the drier may be used for performing drying operations. Since, in addition hereto, another set of
25 hoses cannot be washed as long as a drying operation is effected on a set of hoses previously washed, the capacity of the complete hose cleaning plant has been low.

An object of the invention is to provide an improved drier of the kind initially specified, which
30 facilitates an almost continuous operation of the drier itself as well as of a complete hose cleaning plant wherein the drier is included.

According to the invention, for this purpose, there is provided a drier of said kind, which is primarily characterized in that the receptacle is divided into two parallell drying chambers, extending in side by side relationship along the length of the receptacle and
5 having individually closable longitudinal openings at their upper ends.

By dividing the receptacle of the drier into two parallell drying chambers, as proposed according to the
10 invention, it will be possible, as soon as a drying process in one of said chambers has been completed, to start a drying process in the other drying chamber and, while the latter process takes place, to remove the dried hoses from the firstmentioned drying chamber and then successive-
15 ly to fill it with a new set of washed hoses. The drying operations to be effected in the drying chambers may suitably be obtained by blowing hot air through the hoses as well as around them within said chambers. The necessary equipment for generating hot air and for providing moisture
20 separation, etcetera, may suitably be common to both drying chambers.

Since the drying chambers are intended to operate in an alternating manner, the drier may be provided with a single cover which is common to both drying chambers and
25 adapted to close only one of said chambers at a time. However, according to a preferred embodiment of the invention, the drier may be provided with two covers, one for each drying chambers, in which case the two covers may be connected to each other so as to permit only one drying
30 chamber at a time to be closed by its cover. Such an interconnection between the two covers will make it possible to operate them by means of a common driving element and eliminates the need for separate driving elements for the two covers. Moreover, the two covers may be mounted on a
35 common carrier and be arranged to act as counterweights for each other. Such an arrangement will result in a

reduction of the required driving power for the driving member of the two covers. Both covers may suitably be rigidly mounted on a common rotatable shaft, located between them. In this case, the covers may extend in such
5 directions from said shaft as to form an angle exceeding 90° between their upper surfaces. Said angle may preferably amount to about 120° . The maximum resultant torque on said shaft, caused by the two covers, will then amount to a value corresponding to half the value of the maximum
10 torque on the shaft, caused by one of said covers.

Below the invention will be described in further detail, reference being had to the accompanying diagrammatic drawing in which the single figure shows a perspective cross-sectional view of a drier according to
15 an embodiment of the invention, selected by way of example.

The drier, shown in the drawing, comprises an elongated box-like body of sheet metal, generally designated 10. At its upper end, the drier is provided
20 with two parallel drying chambers 11 which extend in the longitudinal direction of body 10 and are slightly spaced apart in the transversal direction of body 10. Said two drying chambers 11 are formed by elongated tubs 12 having heat-insulated side walls and bottom walls. The longitudinal
25 nal openings provided at the upper ends of drying chambers 11 are individually closable, each by means of an appurtenant cover 13. These two covers 13 are carried by a common shaft 14, located between the two covers and extending in the longitudinal direction of body 10. The two covers 13
30 are rigidly mounted on shaft 14 by means of a number of supporting arms 15 evenly distributed along the length of shaft 14. Between their upper surfaces, the two covers 13 form an angle of about 120° . Reference numeral 16 designates a driving motor for shaft 14, mounted on body
35 10. By means of said motor 16, the two covers 13 may be swung in unison in a manner indicated by double arrow A

to permit one drying chamber 11 at a time to be closed by its appurtenant cover 13. The driving motor 16, which suitably may consist of a hydraulic motor, has been shown to be connected to shaft 14 by means of a chain transmission 17.

- 5 In each drying chamber 11, a grid-like supporting member 18 is provided on some distance above the bottom of the chamber and extending along the whole length of the chamber. On said supporting member 18, a number of hoses 19 may be placed side by side in extended positions to undergo a
- 10 drying operation upon closure of chamber 11 by means of its appurtenant cover 13. The drying operation may suitably be effected by blowing hot air through hoses 19 as well as around said hoses within drying chamber 11. In order to minimize the required energy for heating the drying air, said
- 15 air may suitably be caused to circulate within a closed system, comprising necessary means for separating moisture from the air when leaving the drying chamber. Since the two drying chambers 11 are intended to operate in an alternating manner, said system, which may be common to both drying
- 20 chambers, need not have a larger capacity than required for one of said chambers.




Claims

1. A drier for drying fire-hoses or other similar hoses, said drier comprising an elongated horizontal receptacle, in which a plurality of wet hoses may be placed side by side in extended positions to undergo
5 drying in said receptacle upon closure of the space in which said hoses have been placed, characterized in that the receptacle (10) is divided into two parallel drying chambers (11) extending in side by side relationship along the length of the receptacle and having indivi-
10 dually closable longitudinal openings at their upper ends.
2. A drier according to claim 1, characterized in that it comprises a single cover, which is common to both drying chambers (11) and adapted to close only one
15 of said chambers (11) at a time.
3. A drier according to claim 1, characterized in that it comprises two covers (13), one for each drying chamber (11), said two covers (13) being connected to each other so as to permit only one drying chamber (11)
20 at a time to be closed by its cover (13).
4. A drier according to claim 3, characterized in that the two covers (13) are mounted on a common carrier (14) and arranged to act as counterweights for each other.
5. A drier according to claim 4, characterized in
25 that the two covers (13) are rigidly mounted on a common rotatable shaft (14) located between them, the two covers (13) extending in such directions from said shaft (14) as to form an angle exceeding 90° between their upper surfaces.

6. A drier according to claim 5, characterized in that the upper surfaces of the two covers (13) form an angle of about 120° between them.

BEST AVAILABLE COPY






BEST AVAILABLE COPY



INTERNATIONAL SEARCH REPORT

International Application No PCT/SE80/00247

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) *		
According to International Patent Classification (IPC) or to both National Classification and IPC 3		
A 62 C 33/02, F 26 B 9/06		
II. FIELDS SEARCHED		
Minimum Documentation Searched *		
Classification System	Classification Symbols	
IPC 3	A 62 C 33, B 65 D 43/16; 85/04, B 65 G 21/08, F 26 B 1/00; 3/00, 06; 9/00, 06; 25/06-18	
US C1	217:7, 56-59; 220:243-255, 327-335; 248:89-93 .../...	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched *		
SE, NO, DK, FI classes as above		
III. DOCUMENTS CONSIDERED TO BE RELEVANT ¹⁴		
Category *	Citation of Document, ¹⁵ with indication, where appropriate, of the relevant passages ¹¹	Relevant to Claim No. ¹⁵
A	CH, A, 526 756 published 1972, September 29, Contrafeu AG	1
A	US, A, 756 717 published 1904, April 5, H J Schools	1
A	US, A, 1 108 565 published 1914, August 25, E Feuillette	1
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Special categories of cited documents: ¹⁴</p> <p>"A" document defining the general state of the art</p> <p>"E" earlier document but published on or after the International filing date</p> <p>"L" document cited for special reason other than those referred to in the other categories</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> </div> <div style="width: 45%;"> <p>"P" document published prior to the International filing date but on or after the priority date claimed</p> <p>"T" later document published on or after the International filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search *	Date of Mailing of this International Search Report *	
1981-01-13	1981-01-19	
International Searching Authority *	Signature of Authorized Officer ¹⁰	
Swedish Patent Office	 Nils Andersson	